

27" Widescreen LED Display with Full HD 1080p Resolution





1 Stunning Full HD 1080p

VA2703-LED features Full HD 1080p resolution for incredible, pixel-by-pixel image performance. You'll experience amazing clarity and detail whether you're working, gaming or enjoying the latest video entertainment.

2 Fast ClearMotiv[®] II 3.4ms video response

Innovative ClearMotiv[®] II imaging technology enables an ultrafast 3.4ms liquid crystal response time. Experience digital broadcast-quality, full-motion video with razor-sharp images that never blur.

3 Ultrahigh dynamic contrast ratio

Dynamic contrast ratio automatically detects the brightness of an image and adjusts the LED backlight in response. It maximizes the greyscale and color range and boosts contrast ratio to an ultrahigh 10,000,000:1, resulting in rich, vibrant visuals.

4 LED backlighting

LED backlights enhance display performance by delivering an outstanding contrast ratio to create remarkably refined images. LEDs also provide energy savings and slimmer displays for an all-new entertainment experience.

5 sRGB color management


Accurate and consistent color performance is essential for graphic design, video editing and more. With the built-in sRGB color space, you can easily calibrate the screen to display images in their true colors.

6 Three-phase ECO Mode

Three-phase ECO Mode automatically adjusts display brightness according to the environment. You can also manually choose from three brightness levels to save energy and extend the display's lifetime.



Special Features



The ECO Mode function comes standard with all LED displays. Select from the "Optimize (75%)" or "Conserve (60%)" options to reduce display brightness and save up to 40% energy. Especially under low ambient light conditions, adjusting the brightness will improve visibility by reducing eye fatigue. It will also prolong the display's lamp life, helping you save money and save the planet.







Specifications VA2703-LED						
Item		Content	Item			Content
LCD Panel	Display Area	27" Wide	Power			AC 100-240V (Universal); 50 / 60Hz
	Optimum Resolution	1920 x 1080				30W (Max);17.8W(Eco Mode)
	Brightness	300 cd / m ²	Operating	Tempe	erature	32° F to 104° F (0° C to 40° C)
	Contrast Ratio	1,200 : 1 (typ.)	Conditions	Humic	lity	10% to 90% (No Condensation)
	Dynamic Contrast Ratio	10,000,000 : 1	Dimensions with Stand		(mm)	644 x 436 x 173.7
	Viewing Angles	170° /160° (typ.)	$(W \times H \times D)$		(inch)	25.32" x 17.18" x 6.83"
	Response Time	3.4ms	Dimensions without	ut Stand	(mm)	644 x 390.9 x 55.8
	Pixel Pitch	0.3114mm x 0.3114mm	(W x H x D)		(inch)	25.32" x 15.38" x 2.19"
	Panel Surface	Anti-Glare type, Hardness 3H	Weight	With S	Stand	5.32 Kg (11.73 lbs)
	Backlight	White-light LED		Withou	ut Stand	4.82 Kg (10.62 lbs)
	Backlight Life	30,000 Hrs (Min.)	VESA [®] Mount			100mm x 100mm
Input	Analog	RGB Analog (75 ohms, 0.7 / 1.0 Vp-p)	Accessories			
	Sync	Separate Sync	Accessories			
	Frequency	Fh = 24 - 82 kHz ; Fv = 50 - 75Hz	Power Cord			*1
Compatibility	PC	VSG up to 1920 x 1080 (Non Interlaced)	D-Sub Video Cable			*1
	MAC	Power MAC (Support up to 1920 x 1080)	User Manual			*1
Connector	Analog	15-pin mini D-sub *1	CD Wizard			*1
	Digital	DVI-D *1	*Specifications are subject to change with			iout notice.
	Power	Internal Power Board, 3-pin plug (CEE22) *1				
Ergonomics	Tilt	16° ~ -3°				

ap.viewsonic.com